

MICHELIN X[®] FORCE™ ZL / XZL™



SIZE	TREAD	M+S	RECOMMENDED MEASURING & OPTIONAL RIMS	MASS (+/- 3%)	TREAD DEPTH	OVERALL WIDTH (+/- 3MM)	OVERALL DIAMETER (+/- 4 MM)	STATIC LADEN RADIUS	ROLLING CIRCUMFERENCE (+/- 0.5%)
TL, TT OR TL* (*MAY BE USED WITH TUBE)	LOAD & SPEED INDEX UNIQUE POINT		RUNNING CONDITIONS SINGLE OR DUAL MOUNT	MAXIMUM LOAD & PRESSURE PER TYRE			MAXIMUM SPEED		FOOTPRINT
				KG / KPA	BAR	PSI	KM/H	MPH	CM ²
255/100 R 16 (9.00 R 16) TL* (CAI: 110650)	XZL™ 126 K (134 J)	✓	Measuring 6.50 H Optional 6.00G	39.9 kg	16.5 mm	255 mm	923 mm	426 mm	2810
			Road	1700	4.5	65	110	68	437
			Cross Country	1700	2.9	40	70	43	577
			Mud and Sand	1700	1.7	25	30	19	833
325/85 R 16 TL (CAI: 881538)	X[®] FORCE™ Z 140K	✓	Measuring 9.00	54.7 kg	17 mm	329 mm	983 mm	448 mm	2973
			Road	2500	5.0	72	110	68	564
			Cross Country	2500	3.6	52	70	43	776
			Mud and Sand	2500	1.9	28	30	19	1065
11.00 R 16 TL* (CAI: 109142)	XZL™ 135 K	✓	Measuring 6.50H	49.7 kg	17.5 mm	287 mm	984 mm	455 mm	3000
			Road	2180	5.5	80	110	68	583
			Cross Country	2180	3.2	45	65	40	756
			Mud and Sand	2180	1.7	25	20	12	1010